

DISTRIBUTED BY:

**BARON 817 TEXAS AVE,
EL PASO, TX 79901 915-533-1661**



TECHNICAL DATA SHEET

CHERRY TREE CLEANER - DEGREASER

DESCRIPTION: CHERRY TREE CLEANER - DEGREASER is a concentrated degreaser for industrial, maintenance, kitchen and miscellaneous use. It is a blend of water-soluble solvents, surface-active detergents, water softeners, corrosion inhibitors, and alkaline builders. Its concentrated powerful ingredients will clean everything from painted surfaces to greasy metal parts. Used at full strength for a light oil parts dip, to 60-1 dilution for cleaning mini-blinds, light fixtures, painted woodwork, and many other light duty jobs. CHERRY TREE CLEANER - DEGREASER is designed to be fast acting with maximum safety to the cleaning surface and to the user when used in recommended dilutions.

ADVANTAGES:

- No flash point • Apply with sprayers, pressure washers, by brush, rag,
- Chemically dissolves oil and grease and in steam cleaners
- Contains rust inhibitors • Concentrated, cuts costs
- Use in cold or hot water; hard or soft • Removes soap scum
- Versatile • Cuts through grease, grime, oil, dye, wax, rust, exhaust smoke, scum and dirt

RECOMMENDED USES: CHERRY TREE CLEANER - DEGREASER is recommended for use in schools, restaurants, machine shops, industrial plants, food processing plants, meat packing plants, hotels, motels, automotive, truck and bus maintenance shops. It will clean concrete floors, walls, vents, hoods, ovens, grills, chrome, stainless steel, painted woodwork, fiberglass, Venetian blinds, light fixtures, machinery, equipment, white wall tires, and food processing equipment. Use it as a light duty parts dip, steam cleaner, and a pressure washer cleaner.

DIRECTIONS FOR USE:

INDUSTRIAL USE: Use with one part cleaner to 15 parts water, or more as required. Excellent to clean lathes, milling machines, drill presses and other shop equipment. Use to clean forklifts and other material handling equipment, pumps, conveyors, and many different processing machines. Rinse.

GENERAL BUILDING MAINTENANCE: For mopping waxed floors, use 1 ounce per gallon of water. For heavily soiled concrete use 4 to 8 per gallon of water. Scrub or soak. Remove and rinse floors. Walls: Apply solution of 2 to 4 ounces cleaner per gallon of water for walls and woodwork. Do not use on windows.

KITCHENS: Use solutions of one part cleaner to 10 parts water for removing grease splatter around stoves, vent hoods, fans, and appliances, boil out deep fat fryer, but be sure exhaust fan is on vent hood. Avoid breathing fumes. To soften and remove baked on grease on filters, fans and stove parts, soak overnight, preferably in covered container.

MISCELLANEOUS USES: Use solution of one part cleaner to 15 parts water to clean greasy spots in carpeting, Rinse and clot carpet dry with toweling. Good for removal of black heel marks on flooring, cleaning white sidewall tires, vinyl upholstery, or as a pre-spotter for heavily soiled laundry.

SPECIFICATIONS:

Color	Clear Red
Fragrance.....	Cherry
Residual Film	None after wiping dry
Type of Surfactant	Medium foamer, biodegradable, free rinsing
Flash Point	None
Specific Gravity	1.036 – 1.056
pH @ 77°F.....	12.5 – 13.5
Weight Per Gallon	8.72
Stability & Shelf Life	Excellent

CAUTION: Contains Butyl Cellosolve. May be harmful if swallowed. Do not use in undiluted state. Protect skin and eyes from contact with undiluted product. KEEP OUT OF REACH OF CHILDREN.

Refer to the Safety Data Sheet (SDS) and product label for additional information including Hazard and Precautionary statements, first aid measures, and storage and handling